



Unit : mm

品 號	止 輪 尺 寸 Ring Dimension						適 用 軸 尺 寸 Shaft Dimension (Reference Only)					
	d		D	b	t		d ₁	d ₂		m		n
Ring No.	基本尺寸 Free Dia.	公差 Tol.			基本尺寸 Thickness	公差 Tol.		基本尺寸 Groove Dia.	公差 Tol.	基本尺寸 Width	公差 Tol.	
CT- 12	2.59	+0.05	4.17	0.79	0.4	±0.03	3.2	2.69	±0.04	0.48	+0.04	0.5
18	4.09	-0.1	6.19	1.05	0.4		4.8	4.19		0.48	-0	0.6
21	4.75	+0.07 -0.13	6.99	1.12	0.6		5.6	4.9		0.7	+0.06 -0	0.7
25	5.36		7.90	1.27	0.6	±0.04	6.4	5.59	±0.05	0.7		0.8
31	6.86		9.56	1.35	0.6		7.9	7.01		0.7		0.9
37	8.33		11.37	1.52	0.6		9.5	8.51		0.7		1.0
40	9.12		12.32	1.60	0.6		10.3	9.25		0.7		1.1
43	9.8	±0.15	13.10	1.65	0.6	±0.05	11.1	9.98	±0.07	0.7	+0.08 -0	1.1
46	10.54		14.00	1.73	0.6		11.9	10.69		0.7		1.2
50	11.2		14.76	1.78	0.9		12.7	11.43		1		1.3
56	12.62	±0.18	16.56	1.98	0.9	±0.05	14.3	12.88	±0.07	1	-0	1.4
81	18.31		23.23	2.46	1.4		20.6	18.59		1.5		2.3

*未顯示於表格之規格歡迎來電洽詢

*Other sizes may be available upon request

Copyright (c) 2020 HJ Spring Co., Ltd. All Rights Reserved

◎ 規格標準 Standard Reference

WALDES TRUARC, series 5103

Arcon, series N1800

◎ 材質&硬度(參考) Material & Hardness Ranges (Rockwell scale)

彈簧鋼 · 硬度HRC 44-53 Carbon Spring Steel SAE1050~SAE1090, HRC44~HRC53

不鏽鋼SUS420 · 硬度HRC 36-44 Stainless Steel Type 420, HRC36~HRC44 (Not all sizes in Stainless in stock)

◎ 表面 Finish

原色 Plain

染黑 Black Oxide

鍍鎳 Nickel Plating

◎ 包裝方式 Packaging

散裝 Bulk

條裝 Stacked

(Not all sizes in Stacked in stock)