

Unit : mm

| 品 號           | 止 輪 尺 寸 Ring Dimension |                  |                |                   |            |               |      |      | d <sub>5</sub> | 適用軸尺寸 Shaft Dimension (Reference Only) |                     |                 |               |                |            |         |
|---------------|------------------------|------------------|----------------|-------------------|------------|---------------|------|------|----------------|----------------------------------------|---------------------|-----------------|---------------|----------------|------------|---------|
|               | d <sub>3</sub>         |                  | d <sub>4</sub> | t                 |            | h             | do   | 公差   |                | d <sub>1</sub>                         | d <sub>2</sub>      |                 | m             |                | n          |         |
|               | 基本尺寸<br>Free Dia.      | 公差<br>Tol.       |                | 基本尺寸<br>Thickness | 公差<br>Tol. |               |      |      |                |                                        | 基本尺寸<br>Groove Dia. | 公差<br>Tol.      | 基本尺寸<br>Width | 公差<br>Tol.     | 最小<br>min. |         |
| IS- 6         | 5.6                    | +0.1<br><br>-0.2 | 8              | 0.5               | ±0.04      | 1.2           | 2.2  | ±0.2 | 8.9            | 6                                      | 5.7                 | -0.04           | 0.6           | +0.1<br><br>-0 | 1.5        |         |
| 7             | 6.5                    |                  | 9.3            | 0.6               |            | 1.4           | 2.4  |      | 10.3           | 7                                      | 6.7                 | +0              | 0.7           |                |            |         |
| 8             | 7.4                    |                  | 10.6           | 0.7               |            | 1.6           | 3.0  |      | 11.7           | 8                                      | 7.6                 | -0.06           | 0.8           |                |            |         |
| 9             | 8.4                    |                  | 12             | 0.8               |            | 1.8           | 3.4  |      | 13.1           | 9                                      | 8.6                 |                 | 0.95          |                |            |         |
| 10            | 9.3                    | ±0.15            | 13.3           | 1.0               | ±0.04      | 2.0           | 1.2  | ±0.3 | 14.5           | 10                                     | 9.6                 | -0.09           | 1.15          | ±0.14          |            |         |
| 11            | 10.2                   |                  | 14.4           |                   |            | 2.1           |      |      | 16             | 11                                     | 10.5                | +0<br><br>-0.11 |               |                |            |         |
| 12            | 11.1                   | 15.5             | 2.2            |                   |            | 17.2          |      |      | 12             | 11.5                                   |                     |                 |               |                |            |         |
| 13            | 12                     | 16.6             | 2.3            |                   |            | 18.4          |      |      | 13             | 12.4                                   |                     |                 |               |                |            |         |
| 14            | 12.9                   | 17.5             | 2.3            |                   |            | 19.4          |      |      | 14             | 13.4                                   |                     |                 |               |                |            |         |
| 15            | 13.8                   | 18.6             | 2.4            |                   |            | 20.6          |      |      | 15             | 14.3                                   |                     |                 |               |                |            |         |
| 16            | 14.7                   | 19.7             | 2.5            |                   |            | 21.8          |      |      | 16             | 15.2                                   | 1.35                |                 |               |                |            |         |
| 17            | 15.7                   | 20.9             | 2.6            |                   |            | 23            |      |      | 17             | 16.2                                   |                     |                 |               |                |            |         |
| 18            | 16.5                   | 21.9             | 2.7            |                   |            | 24.2          |      |      | 18             | 17.0                                   |                     |                 |               |                |            |         |
| 19            | 17.5                   | 23.1             | 2.8            |                   |            | 25.4          |      |      | 19             | 18.0                                   |                     |                 |               |                |            |         |
| 20            | 18.5                   | 24.3             | 2.9            |                   |            | 27            |      |      | 20             | 19.0                                   |                     |                 |               |                |            |         |
| <del>21</del> | <del>19.5</del>        | <del>25.4</del>  | <del>3.0</del> |                   |            | <del>28</del> |      |      | <del>21</del>  | <del>20.0</del>                        |                     | +0<br><br>-0.21 |               |                |            |         |
| 22            | 20.5                   | 26.5             | 3.0            | 29                | 22         | 21.0          |      |      |                |                                        |                     |                 |               |                |            |         |
| 24            | 22.2                   | 28.6             | 3.2            | 31.5              | 24         | 22.9          |      |      |                |                                        |                     |                 |               |                |            |         |
| 25            | 23.2                   | 29.8             | 3.3            | 33                | 25         | 23.9          |      |      |                |                                        |                     |                 |               |                |            |         |
| 26            | 24.2                   | 31               | 3.4            | 34                | 26         | 24.9          |      |      |                |                                        |                     |                 |               |                |            |         |
| 28            | 25.9                   | 33.1             | 3.6            | 36.5              | 28         | 26.6          | 1.65 |      |                |                                        |                     |                 |               |                |            |         |
| 30            | 27.9                   | 35.3             | 3.7            | 38.5              | 30         | 28.6          |      |      |                |                                        |                     |                 |               |                |            |         |
| 35            | 32.2                   | 40.6             | 4.2            | 45                | 35         | 33.0          |      |      |                |                                        |                     |                 |               |                |            |         |
| 36            | 33.2                   | ±0.25            | 41.6           | 1.75              | ±0.06      | 4.2           | 2.0  | ±0.4 | 46             | 36                                     | 34                  | +0              | 1.9           | 2.0            |            |         |
| 38            | 35.2                   |                  | 44.0           |                   |            | 4.4           |      |      | 48             | 38                                     | 36.0                | -0.25           |               |                |            |         |
| 42            | 38.5                   | 48.1             | 4.8            |                   |            | 54            |      |      | 42             | 39.5                                   |                     |                 |               |                |            |         |
| 60            | 55.8                   | ±0.45            | 68.4           |                   |            | 2.0           |      |      | 6.3            | 2.5                                    | ±0.5                | 75              | 60            |                | 57.0       | +0/-0.3 |

\*未顯示於表格之規格歡迎來電洽詢

\*Other sizes may be available upon request


Copyright (c) 2020 HJ Spring Co., Ltd. All Rights Reserved



## ◎ 小尺寸規格 Alternative Design

IS-9以下為無孔設計

Special Lug for ring sizes IS-6 thru IS-9



## ◎ 規格標準 Standard Reference

日本工業規格 JIS B 2804

## ◎ 材質&amp;硬度(參考) Material &amp; Hardness Ranges (Rockwell scale)

彈簧鋼 · 硬度HRC 40-50 Carbon Spring Steel SAE1050~SAE1090, HRC40~HRC50

## ◎ 表面 Finish

染黑 Black Oxide

## ◎ 包裝方式 Packaging

散裝 Bulk