


睿盛五金實業股份有限公司


JS Metal Industrial co., Ltd.

TEL:886-2-29955522 FAX:886-2-29950055

● SPP型-空心彈簧銷 SPP SERIES SLOTTED SPRING PINS







																	Uı	nit : mm
	Nomina	l Dia.	1	1.2	1.5	1.6	2	2.5	3	3.5	4	4.5	5	6	8	10	12	13
基本尺寸	D	最大Max.	1.2	1.4	1.71	1.80	2.25	2.75	3.30	3.84	4.40	4.84	5.40	6.40	8.60	10.60	12.50	13.70
	Free Dia.	最小Min. 厚度	X ¹	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1.60	1.70	2.15	2.70	3.20	3.70	4.20	4.70	5.20	6.20	8.30	10.30	12.30	13.40
	t	Thickness	0.3	9.26	0.3	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.2	1.6	2.0	2.0	2.5
	E	最大Max.	0.9	1.1	1.4	1.5	1.9	2.4	2.9	3.4	3.9	4.3	4.8	5.8	7.8	9.8	11.7	12.7
適用孔徑 Hole Dimension		直徑 Dia. 公差 Tol.	/ 1 \	1.2 \ +0.0	1.5 8 / -0	1.6	2.0	+0.09 / -0	3.0	3.5	4.0	4.5 +0.12 / -0	5	6	8	10 5/-0	12 + 0.2	13
品號		公差	. 0.007								al Dia. (Recommended Hole Size)				101107 0 10127 0			- / 0
Pin No.		Tol.	\ 1 /	1.2	1.5	1.6	2	2.5	3	3.5	4	4.5	5	6	8	10	12	13
總長度 Length	SPP - 4	+0.5	\ 0/	\ 0/	0	0	0				-							
	5				0	0	0	0	0									
	6		X	X	0	0	0	0	0	0	0							
	8		A	A	0	0	0	0	0	0	0	0	0					
	10		0	0	0	0	0	0	0	0	0	0	0	0				
	12	+1.0	/	0	0	0	0	0	0	0	0	0	0	0				
	14			, ,	0	0	0	0	0	0	0	0	0	0				
	16				0	0	0	70/	0	0	0	0	0	0	0			
	18				0	0	0	0	0	0	0	0	0	0	0			
	20				0	0	0	0	0	0	0	0	0	0	0	0	0	
	22				0	0	0	0	0	0	0	0	0	0	0	0	0	0
	24				0	0	0	0	0	0	0	0	0	0	0	0	0	0
	25				0	0	0	0	0	0	0	0	0	0	0	0	0	0
						0	0	0	0				0		7			
	28									0	0			0	0	0	0	0
	30						0	0	0	0	0	0	0	0	0	0	0	0
	32						0	0	0	0	0	0	0	0	0	0	0	0
	36						0	0	0	0	0	0	0	0	0	0	0	0
	40						0	0	0	0	0	0	0	0	0	0	0	0
	45						0	0	0	0	0	0	0	0	0	0	0	0
	50						0	0	0	0	0	0	0	0	0	0	0	0
	55										0	0	0	0	0	0	0	0
	60										0	0	0	0	0	0	0	0
	63													0	0	0	0	0
	65											0		0		0		
	70											0	0	0	0	0	0	0
	75											0	_	_	_	0	0	0
	80	+1.5										0	0	0	0	0	0	0
	85	-0														0	0	0
	90														0	0	0	0
	100														0	0	0	0
	110	ł														0	0	0
	120															0	0	0
	125																0	0
	130																	0
	140																0	0
	150																	0

^{*}未顯示於表格之規格歡迎來電洽詢


◆ SPP型-空心彈簧銷


SPP SERIES SLOTTED SPRING PINS



TEL:886-2-29955522 FAX:886-2-29950055







◎ 規格標準 Standard Reference

日本工業規格 JIS B 2808 約略ISO 8752重負荷規格

Equivalent to ISO 8752 (Heavy Duty) but with reduced free diameter for easier assembly

◎ 材質&硬度(參考) Material & Hardness Ranges (Rockwell scale)

彈簧鋼·硬度HRC 44-53 Carbon Spring Steel SAE1050, HRC44~HRC53

不鏽鋼SUS304 · 硬度HRC 36-44 Stainless Steel Type 304, HRC36~HRC44

不鏽鋼SUS420 · 硬度HRC 36-44 Stainless Steel Type 420, HRC36~HRC44

*不鏽鋼製品僅接受訂購·暫無現貨供應 Stainless Steel pins for custom made only.

◎ 表面 Finish

原色 Plain

染黑 Black Oxide

◎ 包裝方式 Packaging

散裝 Bulk

